



14.1 Permissible wheel-tyre combinations



Note

- ◆ *Only tyres of the same size and type may be fitted to the vehicle with front-wheel drive, however the same brand and tread pattern must always be fitted to wheels on the same axle. It is exceptionally allowed to use a different tyre temporarily in the event of breakdown. Take into account a change in driving and braking behaviour.*
- ◆ *Only tyres of the same size, type, brand and tread pattern may be fitted to the vehicle with four-wheel drive. It is exceptionally allowed to use a different tyre temporarily in the event of breakdown. Take into account a change in driving and braking behaviour.*
- ◆ *Use wheel bolts with spherical collar and a thread of M14 x 1.5 - tightening torque: 120 Nm.*
- ◆ *Only use authorised rims on the relevant vehicle.*
- ◆ *When replacing rims always use wheel bolts that belong to these rims (different length and spherical cap shape).*
- ◆ *If winter tyres are used with a lower speed rating than the maximum permissible driving speed, it has to be pointed out with a sticker providing an additional note which must be fixed in the field of vision of the driver.*
- ◆ *The information given on the sticker determines the maximum permissible driving speed for the winter tyres fitted, which must not be exceeded during the operation of the vehicle.*
- ◆ *Note: The note on the sticker can be replaced with the system installed in the vehicle for life (for example the onboard computer) ⇒ Operating instructions .*
- ◆ *Also observe the national legislation.*
- ◆ *On vehicles with the tyre pressure inspection system, it must be adapted again after changing one or several wheels ⇒ Operating instructions .*



Permissible wheel/tyre combinations except for RS and Greenline

Engine	Tyre size	Rim	Offset "OS" (mm)	Snow chains permitted		Number of mounting bolts x bolt-hole circle diameter (mm)	Centre hole diameter (mm)
				Yes	No		
1.2 ltr./63 kW TSI	195/65 R15 91T	6J x 15	43	X		5x112	57
	195/65 R15 91T	6J x 15	47	X			
	205/55 R16 91T	6.5J x 16	46		X		
	205/55 R16 91T	6J x 16	48	X			
	205/55 R16 91T	6J x 16	50	X			
	225/45 R17 91T	7J x 17	49		X		
	205/50 R17 89T	6J x 17	48	X			
	205/50 R17 89T	6J x 17	45	X			
	225/40 R18 92Y	7.5J x 18	51		X		
1.2 ltr./77 kW TSI	195/65 R15 91H	6J x 15	43	X		5x112	57
	195/65 R15 91H	6J x 15	47	X			
	205/55 R16 91H	6.5J x 16	46		X		
	205/55 R16 91H	6J x 16	48	X			
	205/55 R16 91H	6J x 16	50	X			
	225/45 R17 91H	7J x 17	49		X		
	205/50 R17 89H	6J x 17	48	X			
	205/50 R17 89H	6J x 17	45	X			
	225/40 R18 92Y	7.5J x 18	51		X		
1.4 ltr./103 kW TSI	205/55 R16 91V	6.5J x 16	46	X		5x112	57
	205/55 R16 91V	6J x 16	48	X			
	205/55 R16 91V	6J x 16	50	X			
	225/45 R17 91V	7J x 17	49		X		
	205/50 R17 89V	6J x 17	45	X			
	205/50 R17 89V	6J x 17	48	X			
	225/40 R18 92Y	7.5J x 18	51		X		
1.8 ltr./132 kW TSI	205/55 R16 91V	6.5J x 16	46		X	5x112	57
	205/55 R16 91V	6J x 16	48	X			

Engine	Tyre size	Rim	Offset "OS" (mm)	Snow chains permitted		Number of mounting bolts x bolt-hole circle diameter (mm)	Centre hole diameter (mm)
				Yes	No		
	205/55 R16 91V	6J x 16	50	X			
	225/45 R17 91V	7J x 17	49		X		
	205/50 R17 89V	6J x 17	45	X			
	205/50 R17 89V	6J x 17	48	X			
	225/40 R18 92Y	7.5J x 18	51		X		
1.6 ltr./66 kW TDI CR	195/65 R15 91H	6J x 15	43	X		5x112	57
	195/65 R15 91H	6J x 15	47	X			
	205/55 R16 91H	6.5J x 16	46		X		
	205/55 R16 91H	6J x 16	48	X			
	205/55 R16 91H	6J x 16	50	X			
	225/45 R17 91H	7J x 17	49		X		
	205/50 R17 89H	6J x 17	48	X			
	205/50 R17 89H	6J x 17	45	X			
	225/40 R18 92Y	7.5J x 18	51		X		
1.6 ltr./77 kW TDI CR	195/65 R15 91H	6J x 15	43	X		5x112	57
	195/65 R15 91H	6J x 15	47	X			
	205/55 R16 91H	6.5J x 16	46		X		
	205/55 R16 91H	6J x 16	48	X			
	205/55 R16 91H	6J x 16	50	X			
	225/45 R17 91H	7J x 17	49		X		
	205/50 R17 89H	6J x 17	48	X			
	205/50 R17 89H	6J x 17	45	X			
	225/40 R18 92Y	7.5J x 18	51		X		
2.0 ltr./110 kW TDI CR	205/55 R16 91V	6.5J x 16	46		X	5x112	57
	205/55 R16 91V	6J x 16	48	X			
	205/55 R16 91V	6J x 16	50	X			
	225/45 R17 91V	7J x 17	49		X		
	205/50 R17 89V	6J x 17	45	X			
	205/50 R17 89V	6J x 17	48	X			



Engine	Tyre size	Rim	Offset "OS" (mm)	Snow chains permitted		Number of mounting bolts x bolt-hole circle diameter (mm)	Centre hole diameter (mm)
				Yes	No		
	225/40 R18 92Y	7.5J x 18	51		X		
2.0 ltr./105 kW TDI CR	195/65 R15 91H	6J x 15	43	X		5x112	57
	195/65 R15 91H	6J x 15	47	X			
	205/55 R16 91H	6.5J x 16	46		X		
	205/55 R16 91H	6J x 16	48	X			
	205/55 R16 91H	6J x 16	50	X			

◆ Tyre pressure values ⇒ Maintenance ; Booklet Octavia III as well as sticker on the fuel-tank cap

◆ Offset - abbreviation OS

Permissible wheel-tyre combinations version RS

Engine	Tyre size	Rim	Offset "OS" (mm)	Snow chains permitted		Number of mounting bolts x bolt-hole circle diameter (mm)	Centre hole diameter (mm)
				Yes	No		
2.0 ltr./162 kW TSI	225/45 R17 91W	7.5J x 17	51		X	5x112	57
	205/50 R17 89W	6J x 17	48	X			
	205/50 R17 89W	6J x 17	45	X			
	225/40 R18 92Y	7.5J x 18	51		X		
	225/35 R19 88Y	7.5J x 19	51		X		
2.0 ltr./135 kW TDI CR	205/50 R17 89V	6J x 17	45	X			
	205/50 R17 89V	6J x 17	48	X			
	225/45 R17 91V	7.5J x 17	51		X		
	225/40 R18 92Y	7.5J x 18	51		X		
	225/35 R19 88Y	7.5J x 19	51		X		

◆ Tyre pressure values ⇒ Maintenance ; Booklet Octavia III as well as sticker on the fuel-tank cap

◆ Offset - abbreviation OS



Permissible wheel/tyre combinations Greenline version

Engine	Tyre size	Rim	Offset "OS" (mm)	Snow chains permitted		Number of mounting bolts x bolt-hole circle diameter (mm)	Centre hole diameter (mm)
				Yes	No		
1.6 ltr./81 kW TDI CR	185/70 R15 89H	5.5J x 15	47		X	5x112	57
	195/65 R15 91H	6J x 15	43	X			
	205/55 R16 91H	6.5J x 16	46		X		
	205/55 R16 91H	6J x 16	48	X			
	205/50 R17 89H	6J x 17	48	X			
	205/50 R17 89H	6J x 17	45	X			

- ◆ Tyre pressure values = Maintenance ; Booklet Octavia III as well as sticker on the fuel-tank cap
- ◆ Offset - abbreviation OS

